

Technical Data Sheet

Alberdingk® U 400N

Characteristic

Alberdingk® U 400 N is an aliphatic polyether PUD. It is used as a sole binder for high quality leather, artificial leather, textile, paper and plastic coatings due to its excellent hydrolytic stability. It can also be crosslinked with polyisocyanates, aziridines and carbodiamides for a variety of applications.

Features:

- Highly elastic and flexible films
- · Excellent hydrolytic stability

Specification:			According to:
NVW	%	39.0 - 41.0	DIN EN ISO 3251
			1.0 g weighed quantity at
105°C			
pH value		7.0 - 8.0	DIN ISO 976
Viscosity	cps	20 - 200	ISO 1652, Brookfield RVT
			Spindle 1/rpm 20/factor 5

Further typical data*:

Solvent % Solvent free 100% Modulus N/mm2 3.0 Elongation at break % 700

Applications:

Leather coatings Textile coatings Plastic coatings

Latest update March 22, 2014 Alberdingk Boley, Inc. | 6008 High Point Road | Greensboro NC 27407 | Phone +1-336/454-5000 Fax +1-866/220-4750 | info@alberdingkusa.com | www. alberdingkusa.com

page 1 of 2

Alberdingk Boley GmbH | Krefeld, Germany| www.alberdingk-boley.de
Alberdingk Resins (Shenzhen) Co. Ltd. | Shenzhen City, P.R .China | www.alberdingkchina.com



Technical Data Sheet

Alberdingk® U 400N

Storage:

In originally closed containers ALBERDINGK-dispersions are stable when stored at 20°C for 6 months. The recommended temperature-range for storage is 5 - 30°C. Freezing or storage at higher temperatures than 30°C, can affect the viscosity or the average particle size and finally lead to a sedimentation or coagulation. A contamination with bacteria, fungi or algae can damage the product irreversibly.

ALBERDINGK BOLEY Inc. assures that the data mentioned under "specification" are stable for 6 months after delivery date, if the product is stored under the recommended conditions. A longer storage does not mean that the product is not usable anymore, but we recommend to check the specification data before use. A warranty after 6 months of storage cannot be given by ALBERDINGK BOLEY Inc.

Packaging:

drums (460 lbs) totes (2205 lbs) as bulk in tank cars, by agreement.

Safety:

For further information on product safety please refer to the actual material safety data sheet.

Notice:

* General information - the values cannot be considered as part of the product specification.

Latest update March 22, 2014 Alberdingk Boley, Inc. | 6008 High Point Road | Greensboro NC 27407 | Phone +1-336/454-5000 Fax +1-866/220-4750 | info@alberdingkusa.com | www. alberdingkusa.com

page 2 of 2

Alberdingk Boley GmbH | Krefeld, Germany| www.alberdingk-boley.de
Alberdingk Resins (Shenzhen) Co. Ltd. | Shenzhen City, P.R. China | www.alberdingkchina.com